

ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SISTEVEN, S.L.U.

www.sisteven.es

b) Model

f) Thermal efficiency

j) Face velocity at design flow rate

n) Static efficiency of fans according to (EU)

q) Visual filter warning

c) Typology

g) Nominal flowrate

k) Nominal external pressure

327/2011

r) LWA radiated

d) Type of drive

h) Effective electric power input

l) Internal pressure drop of ventilation

o1) Max. Internal leakage index

e) Type of HRS

i) SFPint

m) Internal pressure drop of non-ventilation components

o2) Max. External leakage index
p) Energy performance of the filters

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
				%	m³/s	kW	W/m³/s	m/s	Pa	Pa	Pa	%	%	%			dBA	
CADTM/F-7/7-4M 1/5	NRVU / UVU	Variable Drehzahl	Kein/e		0.279	0.192	230	1.80	198	35		33.2	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-9/9-4M 1/2	NRVU / UVU	Variable Drehzahl	Kein/e		0.546	0.419	230	2.80	286	54		40.7	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-9/9-4M 3/4	NRVU / UVU	Variable Drehzahl	Kein/e		0.555	0.433	230	2.90	269	55		40.2	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-9/9-6M 1/5	NRVU / UVU	Variable Drehzahl	Kein/e		0.445	0.175	230	2.30	81	44		34.1	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-9/9-6M 1/3	NRVU / UVU	Variable Drehzahl	Kein/e		0.462	0.195	230	2.40	90	46		34.2	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-10/10-4M 1/2	NRVU / UVU	Variable Drehzahl	Kein/e		0.692	0.613	230	2.90	393	55		44.5	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-10/10-4M 3/4	NRVU / UVU	Variable Drehzahl	Kein/e		0.666	0.610	230	2.80	413	53		40.9	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-10/10-6M 1/3	NRVU / UVU	Variable Drehzahl	Kein/e		0.581	0.273	230	2.40	157	46		38.7	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-12/12-6T 1 1/2	NRVU / UVU	Variable Drehzahl	Kein/e		0.867	0.601	230	2.60	270	49		42.9	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-12/12-6M 3/4	NRVU / UVU	Variable Drehzahl	Kein/e		0.822	0.577	230	2.50	268	47		45.9	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-12/12-6M 1	NRVU / UVU	Variable Drehzahl	Kein/e		0.849	0.591	230	2.50	256	49		42.2	2.6	G4: G	Siehe Anleitung			2018
CADTM/F-15/15-6T 3	NRVU / UVU	Variable Drehzahl	Kein/e		1.476	1.413	230	3.20	362	61		44.2	2.6	G4: G	Siehe Anleitung			2018