ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SISTEVEN, S.L.U. www.sisteven.es

b) Model
c) Typology
d) Type of drive
e) Type of HRS
f) Thermal efficiency
g) Nominal flowrate
h) Effective electric power input
i) SFPint
j) Face velocity at design flow rate
k) Nominal external pressure
l) Internal pressure drop of ventilation components
m) Internal pressure drop of non-ventilation components
n) Static efficiency of fans according to (EU) 327/2011
o1) Max. Internal leakage index
o2) Max. External leakage index
p) Energy performance of the filters
q) Visual filter warning
r) LWA radiated

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
				%	m^3/s	kW	$W/m^3/s$	m/s	Pa	Pa	Pa	%	%	%			dBA	
CADTM/F-7/7-4M 1/5	NRVU / UVU	Variable Drehzahl	Kein/e		0.279	0.192	230	1.80	198	35		33.2		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-9/9-4M 1/2	NRVU / UVU	Variable Drehzahl	Kein/e		0.546	0.419	230	2.80	286	54		40.7		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-9/9-4M 3/4	NRVU / UVU	Variable Drehzahl	Kein/e		0.555	0.433	230	2.90	269	55		40.2		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-9/9-6M 1/5	NRVU / UVU	Variable Drehzahl	Kein/e		0.445	0.175	230	2.30	81	44		34.1		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-9/9-6M 1/3	NRVU / UVU	Variable Drehzahl	Kein/e		0.462	0.195	230	2.40	90	46		34.2		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-10/10-4M 1/2	NRVU / UVU	Variable Drehzahl	Kein/e		0.692	0.613	230	2.90	393	55		44.5		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-10/10-4M 3/4	NRVU / UVU	Variable Drehzahl	Kein/e		0.666	0.610	230	2.80	413	53		40.9		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-10/10-6M 1/3	NRVU / UVU	Variable Drehzahl	Kein/e		0.581	0.273	230	2.40	157	46		38.7		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-12/12-6T 1 1/2	NRVU / UVU	Variable Drehzahl	Kein/e		0.867	0.601	230	2.60	270	49		42.9		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-12/12-6M 3/4	NRVU / UVU	Variable Drehzahl	Kein/e		0.822	0.577	230	2.50	268	47		45.9		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-12/12-6M 1	NRVU / UVU	Variable Drehzahl	Kein/e		0.849	0.591	230	2.50	256	49		42.2		2.6	G4: G	Siehe Anleitung		2018
CADTM/F-15/15-6T 3	NRVU / UVU	Variable Drehzahl	Kein/e		1.476	1.413	230	3.20	362	61		44.2		2.6	G4: G	Siehe Anleitung		2018