

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SISTEVEN, S.L.U.

www.sisteven.es

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category	[m³/h]	Flowrate	ηe [%]	Efficiency
EC	Efficiency category	[Pa]	Static pressure or total (depending on EC)	N	Efficiency grade
VSD	Variable Speed Drive	[RPM]	Rotation per minute	[kw]	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m³/h]	[Pa]	[RPM]
DTM/B-7/7-4M 1/5-EFF	A	Static	VSD not necessary	1.00	33.4	44.0	0.208	1070	233	1394
DTM/B-12/9-6T 1 1/2-EFF	A	Static	VSD not necessary	1.00	37.2	44.1	0.836	3556	315	853
DTM/B-12/12-6T 1 1/2-EFF	A	Static	VSD not necessary	1.00	38.7	44.8	1.119	4588	340	853
DTM/B-12/12-6M 1-EFF	A	Static	VSD not necessary	1.00	38.3	44.8	0.948	4198	311	852