

ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SISTEVEN, S.L.U.

www.sisteven.es

b) Model

f) Thermal efficiency

j) Face velocity at design flow rate

n) Static efficiency of fans according to (EU)

q) Visual filter warning

c) Typology

g) Nominal flowrate

k) Nominal external pressure

327/2011

r) LWA radiated

d) Type of drive

h) Effective electric power input

l) Internal pressure drop of ventilation

o1) Max. Internal leakage index

e) Type of HRS

i) SFPint

m) Internal pressure drop of non-ventilation components

o2) Max. External leakage index
p) Energy performance of the filters

| b) | c) | d) | e) | f) | g) | h) | i) | j) | k) | l) | m) | n) | o1) | o2) | p) | q) | r) | ERP |
|--------------------------|------------|----------------|------|----|-------|-------|--------|-------|-----|----|----|------|-----|-----|----------------|----------------|-----|------|
| | | | | % | m³/s | kW | W/m³/s | m/s | Pa | Pa | Pa | % | % | % | | | dBA | |
| CADTM/INT-7/7-4M 1/5 | NRVU / UVU | Variable speed | None | | 0.287 | 0.180 | 230 | 5.86 | 197 | | | 33.2 | 2.2 | | Not applicable | Not applicable | 69 | 2018 |
| CADTM/INT-9/9-4M 1/2 | NRVU / UVU | Variable speed | None | | 0.676 | 0.496 | 230 | 8.56 | 277 | | | 40.7 | 2.2 | | Not applicable | Not applicable | 77 | 2018 |
| CADTM/INT-9/9-4M 3/4 | NRVU / UVU | Variable speed | None | | 0.764 | 0.660 | 230 | 9.67 | 341 | | | 40.2 | 2.2 | | Not applicable | Not applicable | 81 | 2018 |
| CADTM/INT-9/9-6M 1/5 | NRVU / UVU | Variable speed | None | | 0.519 | 0.190 | 230 | 6.57 | 116 | | | 34.1 | 2.2 | | Not applicable | Not applicable | 70 | 2018 |
| CADTM/INT-9/9-6M 1/3 | NRVU / UVU | Variable speed | None | | 0.575 | 0.221 | 230 | 7.28 | 126 | | | 34.2 | 2.2 | | Not applicable | Not applicable | 72 | 2018 |
| CADTM/INT-10/10-4M 1/2 | NRVU / UVU | Variable speed | None | | 0.749 | 0.520 | 230 | 7.88 | 263 | | | 44.5 | 2.2 | | Not applicable | Not applicable | 76 | 2018 |
| CADTM/INT-10/10-4M 3/4 | NRVU / UVU | Variable speed | None | | 0.918 | 0.789 | 230 | 9.66 | 348 | | | 40.9 | 2.2 | | Not applicable | Not applicable | 81 | 2018 |
| CADTM/INT-10/10-6M 1/3 | NRVU / UVU | Variable speed | None | | 0.750 | 0.329 | 230 | 7.89 | 154 | | | 38.7 | 2.2 | | Not applicable | Not applicable | 72 | 2018 |
| CADTM/INT-12/12-6T 1 1/2 | NRVU / UVU | Variable speed | None | | 1.423 | 0.997 | 230 | 10.78 | 294 | | | 42.9 | 2.2 | | Not applicable | Not applicable | 85 | 2018 |
| CADTM/INT-12/12-6M 3/4 | NRVU / UVU | Variable speed | None | | 0.847 | 0.660 | 230 | 6.42 | 307 | | | 45.9 | 2.2 | | Not applicable | Not applicable | 74 | 2018 |
| CADTM/INT-12/12-6M 1 | NRVU / UVU | Variable speed | None | | 1.278 | 0.887 | 230 | 9.68 | 286 | | | 42.2 | 2.2 | | Not applicable | Not applicable | 81 | 2018 |
| CADTM/INT-15/15-6T 3 | NRVU / UVU | Variable speed | None | | 0.780 | 0.967 | 230 | 4.08 | 518 | | | 44.2 | 2.2 | | Not applicable | Not applicable | 88 | 2018 |