

ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

SISTEVEN, S.L.U.

www.sisteven.es

- | | | | | |
|------------------|-----------------------------------|---------------------------------------------------------|--------------------------------------|-----------------|
| c) Typology | g) Nominal flowrate | k) Nominal external pressure | 327/2011 | r) LWA radiated |
| d) Type of drive | h) Effective electric power input | l) Internal pressure drop of ventilation components | o1) Max. Internal leakage index | |
| e) Type of HRS | i) SFPint | m) Internal pressure drop of non-ventilation components | o2) Max. External leakage index | |
| | | | p) Energy performance of the filters | |

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
				%	m ³ /s	kW	W/m ³ s	m/s	Pa	Pa	Pa	%	%	%			dBA	
CADTM/ECi-7/7-4M-1/5 IE4	NRVU / UVU	Variable speed	None	0.213	0.115	540	0.00	196		0.0		Not applicable	Not applicable				2018	
CADTM/ECi-7/7-6M-1/10 IE4	NRVU / UVU	Variable speed	None	0.140	0.034	243	0.00	76		0.0		Not applicable	Not applicable				2018	