

ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

| | |
|--|--|
| a) Brand | SISTEVEN, SLU |
| b) Model | CABC-7/7-6M 1/10 |
| c) Specific energy consumption (SEC) average climate (kWh/(m².yr)) | -26.9 |
| c) Specific energy consumption (SEC) cold climate (kWh/(m².yr)) | -54 |
| c) Specific energy consumption (SEC) warm climate (kWh/(m².yr)) | -11.4 |
| c) SEC class | B |
| d) Typology | RVU / UVU |
| e) Drive type | Vitesse variable |
| f) HRS type | Aucun |
| g) Thermal efficiency of heat recovery (%) | |
| h) Maximum flow rate (m³/h) | 414 |
| i) Electric power input of the fan drive at maximum flow rate (W) | 35 |
| j) Sound power level (LWA) (dBA) | 64 |
| k) Reference flow rate (m³/s) | 0.08 |
| l) Reference pressure difference (Pa) | 49 |
| m) SPI (W/m³/h) | 0.105 |
| n) Control factor | 0.65 |
| n) Control typology | Contrôle de la demande locale |
| o) Declared max. internal leakage rate (%) | 0.0 |
| o) Max. external leakage rate (%) | 0.0 |
| p) Mixing rate | 0.00 |
| q) Position and description of visual filter warning | Sans objet |
| r) Instructions to install regulated grilles | Sans objet |
| s) Website | www.sodeca.com |
| t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa | 0.00 |
| u) Indoor/outdoor air tightness | 0.00 |
| v) Annual electricity consumption (AEC) average climate (kWh/yr) | 100 |
| v) Annual electricity consumption (AEC) warm climate (kWh/yr) | 100 |
| v) Annual electricity consumption (AEC) cold climate (kWh/yr) | 100 |
| w) Annual heating saved (AHS) average climate (kWh/yr) | 2800 |
| w) Annual heating saved (AHS) warm climate (kWh/yr) | 1300 |
| w) Annual heating saved (AHS) cold climate (kWh/yr) | 5500 |
| ErP compliance | 2018 |