ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SISTEVEN, S.L.U. www.sisteven.es

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category	**[m^3/h]**	Flow rate	**ηe [%]**	Efficiency
EC	Efficiency category	**[Pa]**	Static pressure or total (depending on EC)	**N**	Efficiency grade
VSD	Variable Speed Drive	**[RPM]**	Rotation per minute	**[kw]**	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m^3/h]	[Pa]	[RPM]
DTT-RE-200-1.5 IE3	B	Totale	L´installation d´un variateur de vitesse n´est pas nécessaire	1.01	53.6	64.9	0.839	1873	863	3900
DTT-RE-200-2 IE3	B	Totale	L´installation d´un variateur de vitesse n´est pas nécessaire	1.01	54.7	64.6	1.135	2089	1074	4350
DTT-RE-250-2 IE3	B	Totale	L´installation d´un variateur de vitesse n´est pas nécessaire	1.01	55.9	65.9	1.116	2543	881	3000
DTT-RE-250-3 IE3	B	Totale	L´installation d´un variateur de vitesse n´est pas nécessaire	1.01	56.1	64.2	1.690	2924	1166	3450