ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SISTEVEN, S.L.U. www.sisteven.es

ERP: Performance at the best efficiency point (BEP).

MC	Measurement category	**[m^3/h]**	Flow rate	**ηe [%]**	Efficiency
EC	Efficiency category	**[Pa]**	Static pressure or total (depending on EC)	**N**	Efficiency grade
VSD	Variable Speed Drive	**[RPM]**	Rotation per minute	**[kw]**	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m^3/h]	[Pa]	[RPM]
DTM/B-7/7-4M 1/5-EFF	A	Statique	L´installation d´un variateur de vitesse n´est pas nécessaire	1.00	33.4	44.0	0.208	1070	233	1394
DTM/B-12/9-6T 1 1/2-EFF	A	Statique	L´installation d´un variateur de vitesse n´est pas nécessaire	1.00	37.2	44.1	0.836	3556	315	853
DTM/B-12/12-6T 1 1/2-EFF	A	Statique	L´installation d´un variateur de vitesse n´est pas nécessaire	1.00	38.7	44.8	1.119	4588	340	853
DTM/B-12/12-6M 1-EFF	A	Statique	L´installation d´un variateur de vitesse n´est pas nécessaire	1.00	38.3	44.8	0.948	4198	311	852