

ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

a) Brand	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU
b) Model	RCS/EC-V-500 F6+F8	RCS/EC-V-500 F7+F9	RCS/EC-H-500 F6+F8	RCS/EC-H-500 F7+F9	RCS/EC-V-700 F6+F8	RCS/EC-V-700 F7+F9	RCS/EC-H-700 F6+F8
c) Specific energy consumption (SEC) average climate (kWh/(m².yr))	-39.2	-39.2	-39.2	-39.2	-40	-40	-40
c) Specific energy consumption (SEC) cold climate (kWh/(m².yr))	-75.6	-75.6	-75.6	-75.6	-76.4	-76.4	-76.4
c) Specific energy consumption (SEC) warm climate (kWh/(m².yr))	-15.7	-15.7	-15.7	-15.7	-16.5	-16.5	-16.5
c) SEC class	A	A	A	A	A	A	A
d) Typology	RVU / BVU	RVU / BVU	RVU / BVU	RVU / BVU	RVU / BVU	RVU / BVU	RVU / BVU
e) Drive type	Diverses vitesses	Diverses vitesses	Diverses vitesses	Diverses vitesses	Diverses vitesses	Diverses vitesses	Diverses vitesses
f) HRS type	Récupératif	Récupératif	Récupératif	Récupératif	Récupératif	Récupératif	Récupératif
g) Thermal efficiency of heat recovery (%)	74	74	74	74	74	74	74
h) Maximum flow rate (m³/h)	482	472	482	472	624	614	624
i) Electric power input of the fan drive at maximum flow rate (W)	339	339	339	339	338	339	338
j) Sound power level (LWA) (dBA)	64	64	64	64	64	64	64
k) Reference flow rate (m³/s)	0.094	0.092	0.094	0.092	0.121	0.119	0.121
l) Reference pressure difference (Pa)	50	50	50	50	50	50	50
m) SPI (W/m³/h)	0.345	0.351	0.345	0.351	0.266	0.27	0.266
n) Control factor	0.65	0.65	0.65	0.65	0.65	0.65	0.65
n) Control typology	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale
o) Declared max. internal leakage rate (%)	1.6	1.6	1.6	1.6	1.7	1.7	1.7
o) Max. external leakage rate (%)	2.6	2.6	2.6	2.6	2.4	2.4	2.4
p) Mixing rate	0.00	0.00	0.00	0.00	0.00	0.00	0.00
q) Position and description of visual filter warning	Voir notice	Voir notice	Voir notice	Voir notice	Voir notice	Voir notice	Voir notice
r) Instructions to install regulated grilles	Sans objet	Sans objet	Sans objet	Sans objet	Sans objet	Sans objet	Sans objet
s) Website	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com
t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa	0.00	0.00	0.00	0.00	0.00	0.00	0.00
u) Indoor/outdoor air tightness	0.00	0.00	0.00	0.00	0.00	0.00	0.00
v) Annual electricity consumption (AEC) average climate (kWh/yr)	163	163	163	163	129	129	129
v) Annual electricity consumption (AEC) warm climate (kWh/yr)	162	162	162	162	128	128	128
v) Annual electricity consumption (AEC) cold climate (kWh/yr)	168	168	168	168	134	134	134
w) Annual heating saved (AHS) average climate (kWh/yr)	4368	4368	4368	4368	4368	4368	4368
w) Annual heating saved (AHS) warm climate (kWh/yr)	1975	1975	1975	1975	1975	1975	1975
w) Annual heating saved (AHS) cold climate (kWh/yr)	8545	8545	8545	8545	8545	8545	8545
ErP compliance	2018	2018	2018	2018	2018	2018	2018

ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

a) Brand	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU	SISTEVEN, SLU
b) Model	RCS/EC-H-700 F7+F9	RCS/EC-V-1000 F6+F8	RCS/EC-V-1000 F7+F9	RCS/EC-H-1000 F6+F8	RCS/EC-H-1000 F7+F9
c) Specific energy consumption (SEC) average climate (kWh/(m ² .yr))	-40	-38.1	-38.1	-38.1	-38.1
c) Specific energy consumption (SEC) cold climate (kWh/(m ² .yr))	-76.4	-74.5	-74.5	-74.5	-74.5
c) Specific energy consumption (SEC) warm climate (kWh/(m ² .yr))	-16.5	-14.6	-14.6	-14.6	-14.6
c) SEC class	A	A	A	A	A
d) Typology	RVU / BVU	RVU / BVU	RVU / BVU	RVU / BVU	RVU / BVU
e) Drive type	Diverses vitesses	Diverses vitesses	Diverses vitesses	Diverses vitesses	Diverses vitesses
f) HRS type	Récupératif	Récupératif	Récupératif	Récupératif	Récupératif
g) Thermal efficiency of heat recovery (%)	74	74	74	74	74
h) Maximum flow rate (m ³ /h)	614	951	925	951	925
i) Electric power input of the fan drive at maximum flow rate (W)	339	839	832	839	832
j) Sound power level (LWA) (dBA)	64	62	62	62	62
k) Reference flow rate (m ³ /s)	0.119	0.185	0.18	0.185	0.18
l) Reference pressure difference (Pa)	50	50	50	50	50
m) SPI (W/m ³ /h)	0.27	0.432	0.44	0.432	0.44
n) Control factor	0.65	0.65	0.65	0.65	0.65
n) Control typology	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale	Contrôle de la demande locale
o) Declared max. internal leakage rate (%)	1.7	1.3	1.3	1.3	1.3
o) Max. external leakage rate (%)	2.4	1.8	1.8	1.8	1.8
p) Mixing rate	0.00	0.00	0.00	0.00	0.00
q) Position and description of visual filter warning	Voir notice	Voir notice	Voir notice	Voir notice	Voir notice
r) Instructions to install regulated grilles	Sans objet	Sans objet	Sans objet	Sans objet	Sans objet
s) Website	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com
t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa	0.00	0.00	0.00	0.00	0.00
u) Indoor/outdoor air tightness	0.00	0.00	0.00	0.00	0.00
v) Annual electricity consumption (AEC) average climate (kWh/yr)	129	208	208	208	208
v) Annual electricity consumption (AEC) warm climate (kWh/yr)	128	207	207	207	207
v) Annual electricity consumption (AEC) cold climate (kWh/yr)	134	213	213	213	213
w) Annual heating saved (AHS) average climate (kWh/yr)	4368	4370	4370	4370	4370
w) Annual heating saved (AHS) warm climate (kWh/yr)	1975	1976	1976	1976	1976
w) Annual heating saved (AHS) cold climate (kWh/yr)	8545	8549	8549	8549	8549
ErP compliance	2018	2018	2018	2018	2018