

sisteven

VENTILATION SYSTEMS





DTM

Double inlet centrifugal fans with direct drive motors and forward impeller



EC CADTM/EC-i

Acoustically insulated ventilation units and EC Technology IE4 motor with integrated electronics



CADTM/ALPS

Ventilation units with double insulating wall, pre-lacquered sheet metal and aluminum profiles



CADT/ALPF

Belt driven ventilation units with pre-lacquered sheet, built-in filters and aluminium profiles




EC CAKS/EC

Ventilation units for circular ducts, with acoustic casing with 25 mm of insulation for noise reduction, interchangeable covers and EC Technology motor



DTR

Belt driven centrifugal fans with double inlet, with reinforced structure and rigid bridge bearings supported on the structure



DT

Belt driven double inlet centrifugal fans with electric motor, pulleys, belts, guards and forward impeller



DTT-RE

Belt driven double inlet centrifugal fans with electric motor, pulleys, belts, guards and backward curved impeller



CADT-RE/ALP

Belt driven ventilation units with aluminium profiles and prefinished sheet steel and acoustic insulation



SS

Low noise, in-line duct extractor fans mounted inside an acoustic casing



REC/EC

Heat recovery units with cross-flow exchanger, automatic control and EC technology motors



UP/EC PCO

Mobile air purifying units with photocatalysis-based technology



CFRT/ALPS FE

Air purifying units with high efficiency electrostatic filters. To be used in oil/greasy applications



UCP/EC FE

Air purifying units with high efficiency electrostatic filters. To be used in oil/greasy applications



TF

Filter units without fan, with different filter options



TST

Cased axial fans 400 °C/2h and 300 °C/2h



SUVT-C

Extraction units 400 °C/2h, with motor and transmission inside the box to work outside the fire zone



SUST

400 °C/2h belt-driven single inlet extractor fan units



TSK

400 °C/2h centrifugal roof fans with horizontal air outlet, aluminum hood



CADTMT

Extraction units and centrifugal double suction fans with direct motor, to work immersed in fire risk areas 400 °C/2h and 300 °C/2h, with the possibility of single-phase motor



SISTEVEN, S.L.U.

B-82071861

Pol. Ind. Miralcampo

Calle Aluminio, 12

19200 AZUQUECA DE HENARES

SPAIN

Tel. +34 91 889 76 13

comercial@sisteven.com

export@sisteven.com

www.sisteven.com